




## AGELESS BEAUTY. UNCOMPROMISED STRENGTH.

## Eternal Collection®

The Eternal Collection encompasses four elegant, inspiring colors exclusive to Steelscape. Providing the same engaging luster as Steelscape's Vintage®, the Eternal Collection expands the breadth of color options available to the design community.

The unique combination of pigmentation and gloss provides a rich, warm color and distinctive surface sheen. Designed to complement the dynamic qualities of the built environment, the Eternal Collection is the perfect finish for roofing and siding applications. Backed by the corrosionresistance of ZINCALUME® and supported by a robust 20-year finish warranty, the Eternal Collection is the durable, yet distinctive finish for your next inspiring building design.



**Ironstone** SRI 29 • 21583



Rainforest SRI 25 • 21584



Sungold SRI 36 • 22070



**Urban Slate** SRI 24 • 21585

Representation of color may vary due to printing limitations. Actual metal samples are available upon request.

Due to the unique nature of this product, color may vary slightly from batch to batch. Batches should not be mixed on projects.





## PERFORMANCE QUALITIES

**Substrate:** (ASTM A792/A792M)

**Thickness:** 

AZ50 ZINCALUME® Coated Steel

`

.0236 (24ga) or .0296 (22ga)

**Steel Grade:** 

80 or 50

Finish:

Durable finish with a proprietary distinctive metallic luster using fluorocarbon pre-paint technology

**Surface Appearance:** 

Smooth and free of blistering and

other surface imperfections

Film Thickness: (ASTM D5796)

Top System Finish: 0.55 – 0.65 mil

Bottom S

Bottom System Finish: Primer = 0.15 – 0.25 mil Backer = 0.30 – 0.40 mil

Specular Gloss: (ASTM D523)

60 Degree Specular Gloss =

5% - 20%; Sungold is 10% - 20%

Hardness: (ASTM D3363)

dness: HB Min

Cure Test: (ASTM D5402)

50 Double MEK Rubs Minimum

Cross Hatch Adhesion: (ASTM D3359) No Tape Off

Reverse Impact: (ASTM D2794)

No Tape Off, 80 inch-pounds of force

T-Bend Flexibility: (ASTM D4145) 2T No Tape Off

**Humidity Resistance:** 

1,000 Hours – Passes

(ASTM D2247)

(100% RH @ 100 degrees F)

Salt Spray Resistance:

1,000 Hours – Passes

(ASTM B117)

(5% Salt Spray @ 95 degrees F)

**Production Location:** 

Rancho Cucamonga, CA